

# iSA6416 RACK Hybrid Windows DVR

- Windows Embedded System
- Full Hybrid Support (Analog and IP)
- Supports 60+ brands of IP cameras
- Supports up to 80 megapixels
- POS Integration
- Inclusion of all AVer Software Features

3U Rack Mountable



*Incredible IP performance in a 16-CH hybrid security DVR packed with the latest AVer features for dependable and durable security deployments*

## IP Performance Matters

The iSA6416 Rack is not only compatible with both analog and IP cameras, but the system is designed to **process massive amounts of video** with extreme power and precision to deliver every meticulous surveillance detail. So there are no jumps, bumps or lags.



## Software Matters

Seamless network integration, intuitive video intelligence, powerful Visual and Intelligent search features, comprehensive remote and alarm management and more, the iSA6416 Rack is built for power, precision and performance.

Award-winning GUI



## Data Safety Matters

The iSA6416 Rack includes our Remote Backup tool that pulls data off the DVRs database and stores the information at a remote location. The system can also be pre-configured for specific time intervals to archive and pull data off.



## POS Matters

When deploying surveillance in retail facilities, **loss prevention** becomes critical. When cash registers are part of the every day work week, you will be happy to know that the iSA6416 Rack is compatible with most commonly used POS systems. Not only does this smart system actively associate transaction data with corresponding video images, but it also outputs alerts for suspicious events based on your assigned keywords.



## Contact Us:

Tel: 678.206.5465  
Fax: 678.206.0123  
Sales@iLinkPro.com


Front Panel Connections			
Front panel controls		Power switch, 3 Removeable HDD	
DVD writer		Included, supported medias: DVD±R, DVD±RW	
USB 2.0 Port		2	
Rear Panel Connections			
Video Inputs (analog)		16 - BNC connectors	
Video Inputs (IP)		16 video H.264/MPEG4/JPEG data streams	
Video Output		1 - VGA out, 1 - DVI/HDMI out, 1 - TV out	
Audio Input/Output		16/1	
Microphone Input		1	
Alarm Inputs/Relay Outputs		4/4	
E-SATA Port		1	
USB 2.0 Port		4	
USB 3.0 Port		2	
AC Power		450 Watt	
Unit			
Operating system		On DOM Windows 7 Pro 64bit	
Compression (analog)		Software: H.264/MPEG4/MJPEG	
Video Format	Analog	NTSC: 352 x 240 (CIF), 640 x 480 (VGA), 720 x 480 (D1)	
	IP	IP/Megapixel Camera Specific	
Recording Rates	Analog	CIF	480fps
		VGA	240fps
		D1	160fps
	IP	Per camera specifications	
Storage	Capacity	Supports up to 5 SATA HDDs (2 Internal, 3 Removable)	
Network		1, 10/100/1000 Base-T Ethernet, RJ-45	
Supported IP cameras (support IP PTZ, IP IO, & IP audio if IP cameras built-in)		AXIS, Panasonic, SONY, Arecont, Mobotix, BOSCH, IQinvision, JVC, TOSHIBA, VIVOTEK, ACTi, D-Link, PiXORD, PELCO, Apron, Lilin and more	
Operator Interface		USB mouse, USB PC keyboard	
Browser/Remote Client		Internet Explorer 6+, Windows 2000, XP, VISTA, 7	
Mechanical			
Dimensions (H x W x D)		5.23 x 18.97 x 20.82in	
Rack Mountable		Optional rack ears	

Software		
Interface		Graphical User Interface
Account Administration		Up to 256 accounts with configurable user privileges
Camera Administration		Add and configure all supported IP/Megapixel cameras through the GUI.
PTZ Control		Zoom-in/Zoom-out, Focus-in/Focus-out, Direction, Speed, Preset point, Autopan
Playback Administration		Playback while recording or setup
		Play, rewind, fast-forward, frame-by-frame control
		Digitally zoom to specific regions in recorded video
		Export single frame to .jpg, export video clip to .DVR/ .AVI/.MPEG
Motion Detection		Configurable to sense mass/motion; can partition off areas in monitoring regions from motion triggers
Event Recording		Scheduled, Continuous, Smart, Motion, Alarm, Manual
Video Event Search		Visual Search, date/time, camera, event & log files
Advanced Event Log		Full event, operation, system & network activities log
Alarm Notifications		Launch or send E-map, relay, video capture, CM3000 or E-mail notification
E-map Display		Positions of cameras, sensors, relays & event status
iEnhance		Enhance video quality such as Brightness/Contrast/ Hue/ Saturation/ Sharpness/ Noise Reduction/De-interlace/ Gray Scale of recorded video
iStable		One-click fix for shaky video caused by camera movement (such as wind or vandalism)
Remote Management		
Central Management		CM3000 software - supports up to 1000 DVRs
Remote DVR connectivity		WebViewer (MS Internet Explorer only), Remote Console, JavaViewer, PDAViewer, iViewer(iPhone/iPad/iPod Touch/ Android)
Dispatch Server		Balance NVR communication for added client access and greater data transfer speeds
DDNS		Allow remote clients to search dynamic servers without enquiring for server's IP address
Environmental		
Temperature	Operating	32 ° to 104 °F
	Storage	-22°F to 140 °F
Relative humidity	Operating	50%-80%
	Stored	90%
Regulatory		
Emissions		FCC: Part 15, Class A
Warranty		
2 Year Limited Parts and Labor		

Front



Rear



- 1 x Spot (RCA)
- 8 x Video (BNC)
- 8 x Audio (RCA)